

3FM190G (6V190AH/10HR)

LONG WAY 3FM190G is one of the Deep Cycle battery of LONGWAY BATTERY.

This series adopts AGM technology, which has high safety & reliability, maintenance-free, high charging rate, low self-discharge, and long life.

Applications: Electric vehicles, Electric scooter, Electric wheel chair, Electric play car for children Sanitation vehicles and police patrol car etc.



Specifications: Designed according with the IEC60254-2014

6Volts (3 Cells per unit) Nominal Voltage

Nominal Capacity @25°C

20hr -rate (9.50A) 220Ah @ 1.75V per cell@25°C (77°F) 209AH @ 1.75V per cell@25℃ (77°F) 10Hr-rate (19.0A) 194AH@1.70Vper cell@25°C (77°F) 5Hr-rate (32.3A) 190AH@1.70Vper cell@25°C (77°F) 3Hr-rate (47.5A)

Weight Approx.31.5± 3%kg(69.42lbs)

Internal Resistance Approx. 1.50mΩ full charged @25°C

Maximum Discharge Current 950A(3sec)

Operating Temperature Range Discharge: -20 °C ~50 °C; Charge: 0 °C ~40 °C

Storage: -20 °C ~40 °C

Equalization and Cycle Service 7.20~7.50VDC/unit Average @ 25°C

Maximum Charging Current 38.0A 17 (M8 stem)

Terminal

Container Material

ABS (UL 94-HB) & Flame Retardant (94-V0)

available upon request

Self Discharge LONGWAY batteries can be stored for more than 6

> months and the Self-discharge ratio less than 3%per month at 25℃. Please charge batteries before using.

ISO9001:2015

ISO14001:2015 ISO45001:2018 ISO50001:2011

APPLICATION STANDARDS

- ISO 7176-25 2013
- IEC 60254-1- 2005
- SAE J1495-2018
- UL1989 (MH46789)

Dimensions


Outer Dimensions







Terminal Type





Cycle Service Life

Length:243 ± 2mm

Width: 187±2mm Height: 274±2mm Total Height: 274±2mm

Capacity Retention Characteristic





Kaiying Power Supply & Electrical Equip Co., Ltd

Add: Laogang Industrial Area, Chengxiang Town, Anxi, Quanzhou City, Fujian Province, China

Tel: 0595-68782266 Fax: 0595-68782222 Web: www.longwaybattery.com Email: sales@longwaybattery.com KY-IOP-EV6-90 B0. August 2023



KY-IOP-LW6-4 A1. October 2014